

Product data sheet

OLIVIA-2 MPL 1500 OP 6800 840 IP66 3H 5X2.5 DALI-2
E010310454
ESYLUX



LED Moisture-proof lights with integrated DALI-2-certified drivers, through-wiring and ENEC test symbol. Safety lighting function 3h Control system: DALI-2 Installation type: Surface mounting Installation position: Ceiling / wall Dimensions: Length 1477 mm x Width 85 mm x Height/Depth 86 mm Weight: 2182 g Protection type: IP66 ApplianceClass: Class I Permissible ambient temperature: 0 °C...+35 °C Colour: light grey, similar to RAL 7035 Nominal voltage: 220 - 240 V AC / 50 - 60 Hz TotalSystemPower: 46 W Luminous flux: 6800 lm Luminous efficacy: 147 lm/W Colour temperature: 4000 K Colour rendering index R_a: >80 Rated lifetime L_{B50} at 25 °C: 102000 h</p><p>ArticleNumber: E010310454 https://www.esylux.com/p/E010310454</p></div>
<div data-bbox="72 417 233 430" data-label="Section-Header"><h2>Light output 1 (integrated)</h2></div>
<div data-bbox="72 435 279 582" data-label="Figure"></div>
<div data-bbox="327 437 903 502" data-label="Table"><table><tr><td>Lamp type</td><td>LED</td><td>CCT</td><td>4000 K</td></tr><tr><td>Nominal lamp power</td><td>46 W</td><td>CRI</td><td>81</td></tr><tr><td>Total flux</td><td>6800 lm</td><td>LOR</td><td>100%</td></tr><tr><td>Luminous efficacy</td><td>148 lm/W</td><td>Total power</td><td>46 W</td></tr></table></div>
<div data-bbox="72 618 170 631" data-label="Section-Header"><h2>Mounting mode</h2></div>
<div data-bbox="72 638 173 651" data-label="Text"><p>Ceiling mounted</p></div>
<div data-bbox="72 661 235 674" data-label="Section-Header"><h2>Shape and measurements</h2></div>
<div data-bbox="72 682 170 729" data-label="Text"><p>Length: 58.15 in
Width: 3.35 in
Height: 3.39 in</p></div>
<div data-bbox="72 739 148 752" data-label="Section-Header"><h2>Adjustability</h2></div>
<div data-bbox="72 760 105 772" data-label="Text"><p>Fixed</p></div>
<div data-bbox="72 783 114 796" data-label="Section-Header"><h2>Design</h2></div>
<div data-bbox="72 803 244 816" data-label="Text"><p>Color of housing: Silver gray</p></div>
<div data-bbox="511 618 557 631" data-label="Section-Header"><h2>Electric</h2></div>
<div data-bbox="511 638 638 702" data-label="Text"><p>System power: 46 W
Ballast: ECG
Controller: DALI
Appliance Class: I</p></div>
<div data-bbox="511 713 575 725" data-label="Section-Header"><h2>Protection</h2></div>
<div data-bbox="511 733 546 762" data-label="Text"><p>IP: 65
IK: 08</p></div>
<div data-bbox="511 773 666 786" data-label="Section-Header"><h2>Other operating numbers</h2></div>
<div data-bbox="511 794 743 807" data-label="Text"><p>Ambient temperature range: 32...95°F</p></div>
<div data-bbox="72 966 241 984" data-label="Page-Footer"><p>Created by luminaires.dialux.com
(12 May, 2025)</p></div>
<div data-bbox="336 966 686 975" data-label="Page-Footer"><p>Technical and design specifications subject to change without notice.</p></div>
<div data-bbox="895 966 950 975" data-label="Page-Footer"><p>Page 1 of 1</p></div>