

Product data sheet


COMPASS SPOT
03.3702 QT-DE-12 200W
FLOS



IP
20


Range of indoor spotlights for accent and general lighting for three-phase track and wall/ceiling installation. Die-cast aluminium alloy, powder-coated optics compartment, diameter 118 mm, composed of an aluminium dissipating element placed above the lamp support, a black thermoplastic screen support ring and 4 mm tempered glass cover. Integrated auxiliary power units for the lamps inside a die-cast aluminium alloy container with powder-coated finish.

Light output 1



1 x Halogen low voltage lamp without reflector

Nominal lamp power	300 W	Socket	R7S
Lamp flux	5000 lm	LOR	86%
Luminous efficacy	21 lm/W	Total flux	4290 lm
CCT	2900 K	Total power	200 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	200 W	Socket	R7S
Lamp flux	3200 lm	LOR	86%
Luminous efficacy	14 lm/W	Total flux	2746 lm
CCT	2900 K	Total power	200 W
CRI	99		

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 2.28 in
Width: 1.57 in
Height: 5.83 in

Adjustability

Free

Electric

System power: 200 W

Protection

IP: 20