# Product data sheet

LUMISTREET GEN2 BGP294 T25 1 XLED280-4S/757 DX70
BGP291
PHILIPS



Time to upgrade your conventional lighting to LumiStreet gen2 Increasing numbers of municipalities are having to upgrade large-scale conventional street lighting installations with energy efficient LED technology. But they are having to do this with smaller and smaller budgets. That's why the new generation of LumiStreet has been upgraded and designed to provide a solution to this challenge, it is the ideal solution for performing point-to-point replacement of conventional lighting. LumiStreet gen2 achieves this by offering high efficiency, low Total Cost of Ownership, and ease of installation and maintenance. The ease of installation and maintenance is enabled by the Philips Service tag. Moreover, the Philips SR (System Ready) socket makes it future-ready and you can pair this luminaire with lighting control and software applications such as Interact City.

## Light output 1



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 164 W | LOR | 72% |
| Lamp flux | 28000 lm | Total flux | 20036 lm |
| Luminous efficacy | 122 lm/W | Total power | 164 W |
| CCT | 5700 K | | |
| CRI | 70 | | |

### Mounting mode

Pole top mounted

### Shape and measurements

Length: 32.01 in
Width: 13.39 in
Height: 5.98 in

### Design

Color of housing: White

### Electric

System power: 164 W

### Protection

Designation labels: CE