Product data sheet

HCC8 LED 8" CYLINDER DOWNLIGHT SERIES
HCC8S15D010BZ-HM81520827-81NDH
COOPER LIGHTING



IP 47

Lumens: 1,500, 2,000, 3,000, 4,000, 6,000 and 8,000, 4 color temperatures: 2700K, 3000K, 3500K, 4000K CCT; CRI: 80 or 90, Distributions: Precision-formed reflectors in Narrow, Medium and Wide, Wall wash distribution with exclusive rotatable linear spread lens, Specular, Semi-Specular and White reflectors; Black or White baffles, Cylinder colors: Matte White, Matte Black, Bronze and Silver, Universal Voltage 120V – 277V; 0-10V analog dimming down to 1%, Mounting: wall, surface, pendant and aircraft cable, L70 at 50,000 hours (70% lumen maintenance at 50,000 hours)

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	13.9 W	CRI	100
Total flux	1232 lm	LOR	100%
Luminous efficacy	89 lm/W	Total power	13.9 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.39 in
Diameter: 8.50 in

Adjustability

Fixed

Electric

System power: 13.9 W

Protection

IP: 47