
Product data sheet

CUBIC MAX SUSPENDED - G2
CG2AEE-840M-Q330-K
LIGHTNET



LED pendant luminaire. Direct-indirect or direct-only light distribution. Luminaire body made of aluminum profile. Surface natural anodised or white, graphite, black or champagne coated as well as polished aluminium. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Microprismatic screen with optimized glare reduction especially for workplaces. Opal diffuser made of acrylic glass. Q1500 and bigger with opal stretch diffuser. Driver integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperature 2700K, 3000K, 3500K or 4000K. Binning initial ≤ Mac Adam 3. Colour rendering CRI>80 or CRI>90. Height-adjustable parallel-cord suspension with transparent power supply cable. On request: Integration of emergency lighting components (only Q430, Q530, Q630), sensor technology, soft-touch black or red sheathed power supply cable.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	12 W	CRI	82
Total flux	1360 lm	LOR	100%
Luminous efficacy	113 lm/W	Total power	12 W

Mounting mode

Pendant

Shape and measurements

Length: 12.99 in
Width: 12.99 in
Height: 2.95 in

Adjustability

Height adjustable

Electric

System power: 12 W

Protection