


Product data sheet

SL720+ PL RXL 60 S/C 8TW GR9006 HCL-S MP
3115968
PERFORMANCE IN LIGHTING



Suspended, LED luminaire for indoor, comprising: Extruded aluminium housing profile, powder-coated. Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP). LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover. Easy, subsequent replacement of the LED modules in just a few simple steps (can also be carried out without an electrician). Direct. Indirect light distribution. Colour rendering index Ra > 80. Colour tolerance according to MacAdam ≤ 3 SDCM. Dimmable via TouchDIM®. With the "OSRAM BT Control" Bluetooth control, the light can be easily configured, personalised or grouped via the app using various parameters. In the tunable white version, the illuminance level and light colour can be manually adjusted from 2700K to 6500K depending on the time of day (DALI DT8). In the HCL version, the illuminance level and light colour can be manually adjusted from 2700K to 6500K depending on the time of day (DALI DT8). Sensor device available with task oriented PIR detector and daylight control. Complete with steel suspension cable (1.5 m), transparent power cord and canopy. VDU application suitable acc. to EN 12464-1. Special colour versions available. Consult factory.

Light output 1



1 x LED			
Nominal lamp power	67 W	LOR	100%
Lamp flux	8043 lm	ULOR	5%
Luminous efficacy	120 lm/W	Total flux	8043 lm
CCT	4000 K	Total power	67 W
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 60.55 in

Width: 9.45 in

Height: 0.79 in

Design

Color of housing: Silver gray

Electric

System power: 67 W

Appliance Class: I

Protection

IP: 20