



Product data sheet

ANDERSON 1 POST TOP LUMINAIRES
AD-20001-W40
LIGMAN



· Lamp COB · CRI Ra > 80 · Mac Adam 3 SDCM · Life time L90B10 Ta 25° C 50,700 · Life time L80B10 Ta 50° C > 65,300 · Colour temperature : 3000K and 4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - White coated indirect shade on the top of luminaire - Anodised, high-purity aluminium reflector - Clear, impact-resistant, UV-stabilised, polycarbonate diffuser

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	40.6 W	CRI	80
Total flux	2997 lm	LOR	100%
Luminous efficacy	74 lm/W	ULOR	6%
		Total power	40.6 W

Mounting mode

Standing / Bollard, Pole top mounted

Shape and measurements

Height: 138.98 in
Diameter: 25.98 in
Weight: 9 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 40.6 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C