
# Product data sheet


TURIS 3.2 D [3000K 11W 230VAC]
TU32115DB
L&L LUCE&LIGHT



IP 40

Recessed downlight for indoor applications; recessed (ceiling); body in black anodized aluminium, trim in steel, screen in one-side-frosted polycarbonate; finish: white, grey, black; 1 multichip power LED; 11W, 15W - 230Vac; power supply unit: included and wired; includes 0,30 m cable; delivered lumen output: 755 lm (3000K, 11W), 1117 lm (3000K, 15W); diffuse optics; LED colour: white - 2700K, 3000K, 4000K; ingress protection: IP40, IP44 installed; operating temperature: 0°C +45°C; screen temperature: max 40°C (Ta 25°C); photobiological safety: risk group 1 in accordance with EN62471:2006; appliance class: II; weight 0,71 kg; dimensions 97x97x76 mm; cut-out size 90x90 mm; overall volume 170x170x130 mm; dimming with DALI, 1-10V, PUSH, mains dimming; accessories: outer casing for solid walls WC3103

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 11 W | CRI | 80 |
| Total flux | 754 lm | LOR | 100% |
| Luminous efficacy | 69 lm/W | Total power | 11 W |

### Mounting mode

Ceiling recessed

### Shape and measurements

Length: 3.82 in
Width: 3.82 in
Height: 3.00 in

### Adjustability

Fixed

### Electric

System power: 11 W
Appliance Class: II

### Protection

IP: 40