

Product data sheet

LED PANEL RGBW


L8000000

PROLED (MBN GMBH)




- slim RGBW LED PANEL - for grid ceiling 625x625mm - dimmable, autom. colour change, controllable via DMX 512, DALI, KNX, 1-10V, CASAMBI, RF by MULTI power supplies/controller - for wall or ceiling mounting (with optional mounting bracket) - for suspension (with optional suspension set) - Supply cable with connector for easy installation

Light output 1 (integrated)




Lamp type	LED	CCT	0 K
Nominal lamp power	9 W	CRI	-29
Total flux	250 lm	LOR	100%
Luminous efficacy	28 lm/W	Total power	9 W

Light output 2 (integrated)




Lamp type	LED	CCT	7247 K
Nominal lamp power	16 W	CRI	-18
Total flux	850 lm	LOR	100%
Luminous efficacy	53 lm/W	Total power	16 W

Light output 3 (integrated)



Lamp type	LED	CCT	0 K
Nominal lamp power	14 W	CRI	-50
Total flux	200 lm	LOR	100%
Luminous efficacy	14 lm/W	Total power	14 W

Light output 4 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	36 W	CRI	80
Total flux	3300 lm	LOR	100%
Luminous efficacy	92 lm/W	Total power	36 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 23.43 in
Width: 23.43 in
Height: 0.39 in
Weight: 3.3 kg

Adjustability

Fixed

Design

Material impression: Matt
Color of housing: White

Electric

System power: 75 W
Controller: Dimmable 1..10V, DMX, DALI
Color adjustable
Appliance Class: III

Protection

IP: 40

Other operating numbers

Ambient temperature range: 14...113°F