Product data sheet


ELLA OUT 3.0 [3000K 19W 230VAC]
EA30105DET
L&L LUCE&LIGHT



IP 65 IK 08

Wall mounted for outdoor applications; surface mounted (wall); body in anticorodal aluminium alloy 6060, screen in microprismatic glass; finishes: anthracite, white, cor-ten, grey; 54 mid power LEDs; 19W - 230Vac; built in power supply unit; includes 1,5 m neoprene cable, H05RN-F 3x1,0 Ø7 mm; total delivered lumens: 1478 lm (3000K); diffuse optics; LED colour: white - 2700K, 3000K, 4000K; ingress protection: IP65; impact resistance: IK08; operating temperature: -10°C +45°C; screen temperature: max 40°C (Ta 25°C); Glow Wire Test: 960°; photobiological safety: risk group 1 in accordance with EN62471:2006; appliance class: I; weight 1,20 kg; dimensions 294x80x29 mm; accessories: spacer for 15° inclination WD0653E / WD0653F / WD0653H / WD0653R

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	19 W	CRI	80
Total flux	1478 lm	LOR	100%
Luminous efficacy	78 lm/W	Total power	19 W

Mounting mode

Wall mounted

Shape and measurements

Length: 11.57 in
Width: 3.15 in
Height: 1.14 in

Adjustability

Fixed

Electric

System power: 19 W
Appliance Class: I

Protection

IP: 65
IK: 08