



Product data sheet

INDUSTRIAL AND WAREHOUSE LIGHTING
V1-I0-70588-05A06-6505040 AXIUM 1,3 M 50W 4000K TEMPERED GLASS EM 1H
VARTON



Industrial linear luminaire with facilities with high chemical resistance and hygienic requirements. Stainless steel housing, tempered glass or PMMA (acrylic) diffuser. Installation: Suspended and surface-mounted. Suspended by eye nut (included in package) Application: Suitable for facilities with chemically aggressive environment, food processing halls, and fire hazardous zones classified as P-IIa according to Electrical Installations Regulations. Power factor: 0,95 Input voltage (AC, 50Hz), V: 198...264 AC frequency, Hz: 50 Protection class: I Impact resistance: IK08 Input voltage (DC), V: 176...280 Flicker, %: 5 Climatic modification and category of placement: УХЛ1 Ingress protection (IP): IP65 <https://www.varton.ru/products/promyshlennoe-i-skladskoe-osveshchenie/axium/axium-1-3-m/svetodiodnyy-svetilnik-var-ton-axium-1-3m-50-vt-4000-k-rasseivatel-zakalennoe-steklo-avariynyy-avtono/>

Light output 1



1 x LED			
Nominal lamp power	50 W	LOR	100%
Lamp flux	5600 lm	Total flux	5600 lm
Luminous efficacy	112 lm/W	Total power	50 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Electric

System power: 50 W

Shape and measurements

Length: 51.18 in

Width: 8.27 in

Height: 3.54 in

Protection

IP: 65

IK: 08

Adjustability

Fixed