Product data sheet

VOLKMAR II (WALL FITTING) 9.840.0080.05

LEIPZIGER LEUCHTEN









For medium light requirements, mounting heights from 3.00 - 4.00 m. - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant clear polycarbonate attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection -Available in any RAL - or DB -colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure mercury vapour lamp		
Nominal lamp power	125 W	
Lamp flux	6800 lm	
Luminous efficacy	42 lm/W	
CCT	3400 K	
CRI	54	

LOR	85%
ULOR	28%
Total flux	5755 lm
Total power	137 W



I x High pressure mercury vapour lamp			
Nominal lamp power	80 W	LOR	
Lamp flux	4000 lm	ULOR	
Luminous efficacy	38 lm/W	Total flux	
CCT	3400 K	Total power	
CRI	54		

Mounting mode

Wall mounted

Shape and measurements

Height: 16.14 in Diameter: 16.14 in Electric

System power: 89-137 W

Protection

IP: 55

85% 28% 3385 lm 89 W