


Product data sheet

O66-W1225 LED 5000 830 ASY
GLAMOX



Light source LED 1300 - 5200 lumen out Colour temperature 3000/4000 K, CRI Ra 80, MacAdams 3 RGB-W on request Driver Fixed output (HF) or DALI dimmable. Body material & colour Body in extruded and die-cast aluminium. Double layer polyester powder coated paint finish. Available in two different colours; aluminium grey (RAL 9006) or anthracite (close to RAL 7024). Tempered front glass. Silicone gasket. Screws made of stainless steel. Mounting On wall, ceiling or solid ground by use of brackets that have to be ordered separately. The luminaire can both be single and continuous mounted and is equipped with a goniometric system, permitting continuous adjustments at constant steps of 5°. Accessories Wall brackets of galvanized and painted steel. Connection 2 x M20 cable glands (cable Ø8 - 12 mm) on connection box at the backside of the luminaire. 3/5 pole 6 mm² screw terminal block. Outdoor use requires suitable flexible cables assuring the water tightness of the cable gland. Optics Medium beam (MB). Narrow beam (NB).

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	56 W	CRI	80
Total flux	5000 lm	LOR	100%
Luminous efficacy	89 lm/W	ULOR	84%
		Total power	56 W

Mounting mode

Wall mounted

Shape and measurements

Length: 48.23 in
Width: 4.09 in
Height: 3.43 in

Adjustability

Tiltable

Design

Color of housing: Anthracite / graphite, Silver gray

Electric

System power: 56 W

Protection

IP: 66
IK: 09