Product data sheet


CUT-5 LED 36 4000K T2
216032/4/T2/10KV
ROSA



IP 66

Lighting set with a simple shape. Made of aluminium - the standard version is anodised in inox and grey. Designed to illuminate city roads and residential streets, office buildings' surroundings, parks and pedestrian routes. It has a protection class of IP 66 for the optical part and the power input system. The set is equipped with PMMA lenses and an interchangeable LED module. The expected service life of the product is L90B10 - 100,000 h. The input voltage frequency is 50/60Hz. Power factor ≥0.95. Depending on the power variant, the set has: 12 LEDs (for 12W, 24 W, 36 W), 24 LEDs (for 48 W, 72 W). It is possible to connect the set to an external control system via the DALI interface (optional support for an analogue 1-10V signal).

Light output 1



1 x LED

Nominal lamp power	40 W	LOR	82%
Lamp flux	6150 lm	Total flux	5044 lm
Luminous efficacy	154 lm/W	Total power	40 W
CCT	4000 K		
CRI	70		

Mounting mode

Pole integrated, Pole top mounted

Shape and measurements

Length: 31.50 in
Width: 5.91 in
Height: 3.74 in

Adjustability

Fixed

Electric

System power: 40 W

Protection

IP: 66