


Product data sheet

WATERFRONT ALU COLOUR TEXT, LED 28W / 3000K
5747701023
LOUIS POULSEN



Waterfront Design : Dan Borgen Hasløv Light concept : The fixture emits 100% glare-free downward light. The light distribution is symmetric and soft. The four supports create an comfortable symmetric light pattern at ground level. Finish: Aluminium coloured with textured surface or graphite with textured surface, powder coated. Material: Enclosure: Injection moulded clear polycarbonate. Housing: Die cast aluminium. Top: Die cast aluminium. Post: Extruded aluminium. Base plate: Die cast aluminium. Mounting: In-ground struts: Yes. Terminal block positioning: In fixture head. Looping: Approved, max 5x2,5mm². Ballast positioning: In fixture head. Max. installation cable: 1 or 2x5x2,5mm² or depending on installation box. Post f/in-ground installation: H: 1195mm excl. fixture head, in-ground part: 600mm. Post w/ base plate for surface mounting: H: 595mm excl. fixture head. Post dia. 210mm. Weight: Max. 18.5 kg. Class: Ingress protection IP55. Electric shock protection I w. ground, II w/o ground. IK 10.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	28 W	CRI	80
Total flux	670 lm	LOR	100%
Luminous efficacy	24 lm/W	ULOR	9%
		Total power	28 W

Mounting mode

Standing / Bollard

Shape and measurements

Height: 44.69 in

Diameter: 10.24 in

Adjustability

Fixed

Electric

System power: 28 W

Appliance Class: I

Protection

IP: 55

IK: 10