


Product data sheet

M - LED LINE HE 1 X 25,2W DIM5
23350 0005
DELTA LIGHT



Luminaire, low voltage systems low voltage system mounted (indoor use) from Deltalight, named M - LED LINE HE 1 x 25,2W DIM5, available in the colour(s): black. This luminaire can be used with the following 48V magnetic lighting system(s): SHIFTLINE M26H - PROFILE, SHIFTLINE M26H + SBL, SHIFTLINE M26L - PROFILE, SPLITLINE M20 - PROFILE, SPLITLINE M20 ST - PROFILE. This luminaire is equipped with LED flex 25,2W / CRI>90 (R9: 60) / 3000K / 3000lm with build-in converter to operate on a voltage of 48V-DC. Dimming protocol: DALI. Light distributor: opal diffuser.

Light output 1



1 x LED			
Nominal lamp power	29 W	LOR	73%
Lamp flux	3000 lm	Total flux	2182 lm
Luminous efficacy	103 lm/W	Total power	29 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling mounted, Contact rail, Wall mounted, Pendant, Wall recessed

Shape and measurements

Length: 47.64 in
Width: 0.71 in
Height: 0.04 in
Weight: 0.7 kg

Electric

System power: 29 W
Appliance Class: II

Protection

IP: 20
Designation labels: CE