Product data sheet

LP SLIM ROUND SURFACE MOUNTED Ø440 WHITE LED 3000K 35W PRISM HO 5742585299

LOUIS POULSEN








LP Slim Round Design: Louis Poulsen A/S Concept: The slim housing encircles and high-efficient acrylic diffuser emitting diffused primarily downward directed light. The slim body has a slight curvature and an inner curve which reduces contrast. The product family comes in a range of sizes and mounting options for a wide range of applications. Surface mounted and suspended versions have an indirect light component. Finish: White, aluminium grey or black, powder coated. Material: Reflector: Die cast aluminium. Diffuser: Acrylic, opal. Installation lock: Aluminium. Mounting: Ceiling thickness: 1–60 mm. Cut-out dimensions Ø 250: Ø234mm Ø 440: Ø425mm Ø 680: Ø 666mm. Optional wire for alternative installation. Looping: Approved, max 5x1.5mm2. Driver integrated. Weight: Max: 8.8 kg Class: Ingress protection IP20. Electric shock protection I.

Light output 1



1 x LED		
Nominal lamp power	35 W	LOR
Lamp flux	3617 lm	Total flux
Luminous efficacy	72 lm/W	Total power
CCT	3000 K	
CRI	90	

Mounting mode

Ceiling mounted

Shape and measurements

Height: 1.85 in Diameter: 17.32 in

Adjustability

Fixed

Electric

System power: 35 W Appliance Class: I

Protection

IP: 20

69% 2503 lm 35 W