Product data sheet


ANDHO MIDI MAST
722280.002.2.76
RZB



IP 65 IK 08

Series: ANDHO midi Housing made of corrosion-resistant die-cast aluminium with extension arm, seawater-resistant powder-coated (C4, in accordance with ISO 12944-6). C5 coating available on request. Stainless steel screws. With membrane valve as a standard to avoid condensed water. Rotation-symmetric reflector made of reflex-boosted MIRO-SILVER. Cover clear single-pane toughened glass. Light distribution: Spot, medium beam. Pole mounting by means of 1 drilled hole Ø 24 mm (provided on site). Rotation angle: Up to 360° stepless, tilt angle 90° in increments of 5°, angle scale can be adjusted and locked. Converter integrated in the luminaire head. Spotlight with 8 m connecting cable. Colour: traffic white, matt (RAL 9016) Length: 261 mm Width: 154 mm Height: 216 mm Lamp: LED System power: 39 W Rated luminous flux: 4700 lm Luminous efficiency: 121 lm/W Control gear: Converter, dimmable, DALI Protection class: II Type of protection: IP 65

Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	39 W	CRI	80
Total flux	4700 lm	LOR	28%
Luminous efficacy	121 lm/W	ULOR	8%
		Total power	39 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 6.06 in
Width: 11.50 in
Height: 8.50 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 39 W

Protection

IP: 65
IK: 08