


Product data sheet

DIGISTREET BGP762 T25 1 XLED220-4S/757 DM11
BGP760
PHILIPS



Get your city ready for the future with DigiStreet. Developed with the aim to become your long term partner, the system ready architecture of DigiStreet enables you to enjoy the benefits of connected lighting systems today and also gets the city ready for the innovations to come!. Its two sockets enable you to connect directly to the Philips CityTouch system and is also prepared to connect you to the future innovations of IoT. Next to this, each individual luminaire is uniquely identifiable, thanks to the Philips Service tag application. With a simple scan of a QR code, placed on the inside of the mast door, you gain instant access to the luminaire configuration, making maintenance and programming operations faster and easier, no matter what stage of the luminaire's lifetime. DigiStreet is also equipped with dedicated light recipes that: 1) maintain an optimal ecosystem for bats or 2) preserve a dark night sky.

Light output 1



1 x LED			
Nominal lamp power	130 W	LOR	89%
Lamp flux	22000 lm	Total flux	19546 lm
Luminous efficacy	150 lm/W	Total power	130 W
CCT	5700 K		
CRI	70		

Mounting mode

Pole top mounted

Electric

System power: 130 W

Shape and measurements

Length: 33.86 in
Width: 14.21 in
Height: 4.21 in