# Product data sheet

CLARA VII (OPAL ATTACHMENT) 9.767.3062.00

LEIPZIGER LEUCHTEN






CE

For medium/high light requirements, mounting height 4.00 – 7.00 m. - Impact-resistant clear/opal polycarbonate attachment,UV- stabilized - High-pressure lamps with coated bulbs use reflector lamellae made of premium highest-grade aluminium, burnishid and anodized, for light guidance and glare limitation - Computer-optimized reflector system for high-pressure lamps with clear glass tubular bulbs ensures excellent illumination -Aluminium reflector finished in special white paint for max. light reflection - Corrosion-resistant cast aluminium unit carrier, painted - All electrical components on one block - Adapter jack connection -Available in any RAL or DB colour without surcharge - for post dia. 76mm; order post dia.76mm separately

## Light output 1



I x High pressure mercury	vapour lamp
Nominal lamp power	125 W
Lamp flux	6800 lm
Luminous efficacy	29 lm/W

Luminous efficacy 29 lm/W CCT 3400 K CRI 54

LOR 58% ULOR 13% Total flux 3918 lm Total power 137 W

#### Mounting mode

Pole top mounted

## Shape and measurements

Height: 27.56 in Diameter: 29.92 in

# Design

Material impression: Matt Color of housing: Black

### Electric

System power: 137 W

Ballast: ECG Controller: DALI

#### Protection

Designation labels: CE

#### Other operating numbers

Ambient temperature range: -13...95°F