

# Product data sheet


6502 RAPID SYSTEM - TWO-LAMP LED 4000K CRI 83 71W CLD-E WHITE + 6414 RAPID SYSTEM CONCENTRIC PARABOLIC 237543-07+237765-00

DISANO



Housing: in galvanized rolled steel, with anti-cutting turned-up edges and ABS end caps. Diffuser: micro-ribbed methacrylate Coating: pre-painted in oven with polyester resin, UV-stabilised, phosphate pre-treatment. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Equipment: -fixing pawl in nylon. - LED tubes can be rotated to direct the light and optimise the output of the optical accessories. Mounting: ceiling or wall mount Temperature Chart (Description): -10 °C ÷ +40 °C

## Light output 1 (emergency)



1 x LED			
Nominal lamp power	71 W	LOR	100%
Lamp flux	7733 lm	Total flux	7724 lm
Luminous efficacy	109 lm/W	Total power	71 W
CCT	4000 K		
CRI	83		

## Mounting mode

Pendant

## Shape and measurements

Length: 58.50 in

Width: 9.96 in

Height: 5.08 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 71 W

Appliance Class: I

## Information regarding emergency functions

Emergency lighting only

Emergency sign: N/A

## Protection

IP: 40

IK: 07

Designation labels: CE