Product data sheet

OFFICE LUMINAIRES FOR SPECIAL CEILINGS
V1-C1-00083-10G06-5403640 AL220 IP54 (1170*100MM) 35W 4000K OPAL
VARTON



IP 54 IK 08

Luminaire for rack ceiling system with increased ingress protection. Stainless steel housing with white powder coating. Application: healthcare, food outlets, laboratories, washrooms, hospitality (restaurants, hotels, coffee bars). Suitable for areas with high moisture and dust protection requirements Installation. Recessed mounted compatible with rack ceiling with rails of Italian and German design. Input voltage (AC, 50Hz), V: 176...264 AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: УХЛ2 Height/depth, mm: 70 Length, mm: 1 325 Protection class: I Ingress protection (IP): IP54 Impact resistance: IK08 Width, mm: 308 Power factor: 0,95 https://www.varton.ru/products/ofisnye-svetilniki-dlya-nestandartnykh-potolkov/al-svetilniki-dlya-reechnykh-potolkov/al270-ip54-reechnyy-p-k-1325-308-analog-2-36/svetodiodnyy-svetilnik-varton-dlya-reechnogo-potolka-1325kh308-36-vt-4000-k-ip54-s-zashchitnym-silik/

Light output 1



1 x LED

Nominal lamp power	36 W	LOR	100%
Lamp flux	3100 lm	Total flux	3100 lm
Luminous efficacy	86 lm/W	Total power	36 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 52.17 in
Width: 12.13 in
Height: 2.76 in

Adjustability

Fixed

Electric

System power: 36 W

Protection

IP: 54
IK: 08