


Product data sheet

LTUB60 SU RE 1120 3000 NW OPAL BK
L61SE112MOOP940NB
LAMP



Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 1120mm, with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 4000K with CRI 90. Built-in electronic ON/OFF control gear. With IP20, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Light output 1



1 x LED			
Nominal lamp power	25.4 W	LOR	100%
Lamp flux	2126 lm	Total flux	2125 lm
Luminous efficacy	84 lm/W	Total power	25.4 W
CCT	4000 K		
CRI	90		

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 45.35 in
Width: 2.76 in
Height: 2.56 in

Adjustability

Fixed

Design

Color of housing: Black, White

Electric

System power: 25.4 W
Appliance Class: I

Protection

IP: 20
IK: 07