Product data sheet


COLUMN LUMINAIRE RESIDENZA-2 C M8 16LED 3000K
88.00900.0V0XX + 99.20944.1V00X
HESS



IP 65


Illuminating column made of aluminium, consisting of top element and base element. Protective cover and luminaire glass made of clear PC glass. Light source sits on four aluminium rods. Cylindrical luminaire body made of cast aluminium. Diameter 200 mm. Total height of columns including luminaire 4600 mm

Light output 1




1 x LED

Nominal lamp power	33.9 W	LOR	100%
Lamp flux	4286 lm	Total flux	4286 lm
Luminous efficacy	126 lm/W	Total power	33.9 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	27.1 W	LOR	100%
Lamp flux	3435 lm	Total flux	3435 lm
Luminous efficacy	127 lm/W	Total power	27.1 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	31.6 W	LOR	100%
Lamp flux	4007 lm	Total flux	4007 lm
Luminous efficacy	127 lm/W	Total power	31.6 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	24.8 W	LOR	100%
Lamp flux	3140 lm	Total flux	3140 lm
Luminous efficacy	127 lm/W	Total power	24.8 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	22.5 W	LOR	100%
Lamp flux	2839 lm	Total flux	2839 lm
Luminous efficacy	126 lm/W	Total power	22.5 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	20.2 W	LOR	100%
Lamp flux	2534 lm	Total flux	2534 lm
Luminous efficacy	125 lm/W	Total power	20.2 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	2220 lm	Total flux	2220 lm
Luminous efficacy	123 lm/W	Total power	18 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	15.7 W	LOR	100%
Lamp flux	1897 lm	Total flux	1897 lm
Luminous efficacy	121 lm/W	Total power	15.7 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	13.4 W	LOR	100%
Lamp flux	1567 lm	Total flux	1567 lm
Luminous efficacy	117 lm/W	Total power	13.4 W
CCT	3000 K		
CRI	80		



1 x LED

Nominal lamp power	11.1 W	LOR	100%
Lamp flux	1225 lm	Total flux	1225 lm
Luminous efficacy	110 lm/W	Total power	11.1 W
CCT	3000 K		
CRI	80		



1 x LED

Nominal lamp power	29.4 W	LOR	100%
Lamp flux	3724 lm	Total flux	3724 lm
Luminous efficacy	127 lm/W	Total power	29.4 W
CCT	3000 K		
CRI	80		

Mounting mode

Standing / Bollard, Pole top mounted

Shape and measurements

Length: 10.76 in
Width: 10.76 in
Height: 183.38 in

Adjustability

Fixed

Electric

System power: 11.1-33.9 W

Protection

IP: 65