Product data sheet

HL36SA LED 3" SQUARE NEW CONSTRUCTION DOWNLIGHT
HL36AR20SP935ED010TL3PINMWWB-TILTED 30D
COOPER LIGHTING



IP 47

Suitable for 2x6 residential or shallow plenum commercial, Broad range of trims; Optional adapter allows rimless installation, Field-interchangeable optics: 15°, 25°, 40° and 55°, Locking 365° rotation and 45° tilt holds any aiming position, Translating center beam optics aligns primary reflector with aperture, Got Nail!™ bar hangers; Insulated Ceiling (IC) rated, Available in 2700K, 3000K, 3500K, 4000K, or Dim-to-warm, Universal Voltage 120V-277V; phase cut or 0-10V dimming down to 1%, 3 wattage options and 3 driver options (details on spec sheet)

Light output 1 (integrated)



Lamp type	LED	CCT	3500 K
Nominal lamp power	19.7 W	CRI	90
Total flux	1133 lm	LOR	100%
Luminous efficacy	58 lm/W	Total power	19.7 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.39 in
Diameter: 2.00 in

Adjustability

Fixed

Electric

System power: 19.7 W

Protection

IP: 47