Product data sheet

LINA45-S 145S-2C0K-25GGM3/830, S 145S-2C0K-25GGM3/830


HALLA



IP 20


145S-2C0K-25GGM3/830, S Luminaire surface/suspended Material of luminaire: Colour of luminaire: Shape of luminaire: Linear Size: 1403 x 47 x 69 mm Type of installation: Surface, Suspended Distribution: Direct Optics type: Opal diffuser Protection class: I Voltage: 220-240V

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1.5 W	CRI	80
Total flux	280 lm	LOR	100%
Luminous efficacy	187 lm/W	Total power	1.5 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	19.8 W	CRI	80
Total flux	2990 lm	LOR	100%
Luminous efficacy	151 lm/W	Total power	19.8 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 1.85 in

Width: 55.24 in

Height: 2.72 in

Adjustability

Fixed

Electric

System power: 21.3 W

Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 20