

Product data sheet


LEDSPOTRA-HJII 10W-4000-36°-WH
541003182410
OPPLE



IP
20

Housing: Aluminum+PC; Mounting ring: white; Installation: recessed; Dimensions: $\Phi 85 \times 57 \text{ mm}$; Ceiling cutouts: $\Phi 75 \text{ mm}$; Beam angle: 36° ; Lamp(s): LED; Power: 10W; Efficacy : 100lm/w; Total luminous flux of luminaire: 1000lm; Power Factor: 0.9; Mains voltage: 220-240V/50-60Hz; Colour temperature: 4000K; Colour rendering: Ra80; UGR: 22; IP/IK Grade: IP20; Class of protection II; Control System: on/off, DALI, 1-10V, BLE; Service life: 30,000h at 70% luminous flux;

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	10.37 W	CRI	80
Total flux	1000 lm	LOR	100%
Luminous efficacy	96 lm/W	Total power	10.37 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.35 in

Width: 3.35 in

Height: 2.24 in

Adjustability

Free

Electric

System power: 10.37 W

Protection

IP: 20