Product data sheet

FLEXBAR SURFACE / SUSPENDED - 20W (14W/M) - INDIVIDUAL - 1400MM - UP & DOWNLIGHT - METALLISED REF - 4000K. EFR20MVUM


THORLUX LIGHTING



IP 20


Flexbar is an elegant surface mounted or suspended linear luminaire ideal for a wide range of applications. The high performance lens technology provides well-controlled low glare lighting for optimum user comfort. Individual and continuous versions along with corner joints allow the lighting designer to be creative with their lighting layouts. Supreme efficiency (160.5 LL/cW) and 100,000 hour life ensures Flexbar has the performance to match its beauty. Applications: Offices, teaching spaces, meeting rooms, breakout areas, reception areas, circulation spaces and retail

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	23 W	CRI	80
Total flux	3510 lm	LOR	100%
Luminous efficacy	153 lm/W	Total power	23 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	23 W	CRI	80
Total flux	3510 lm	LOR	100%
Luminous efficacy	153 lm/W	ULOR	17%
		Total power	23 W

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 55.12 in
Width: 1.73 in
Height: 2.40 in

Adjustability

Fixed, Height adjustable

Electric

System power: 46 W

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 20