


# Product data sheet

CYCLOPS - DOUBLE SIDED  
7172-K-5-572-XX  
UNILAMP



Cyclops family is an innovative walkway lighting solution with shielded light sources. Delivering light exactly where it is needed without disruptive glare. Operated with multiple LED with built in heat sink. The light is precisely controlled by clear asymmetric lenses and is directed onto the illuminated surface. The vandal resistant clear polycarbonate cover protects the bollard from harmful dust and water. It is available in two sizes and two heights with 180 and 360-degree light distribution. CYCLOPS can be installed in residential areas, walkways, parks, commercial areas and open spaces. It provides illumination for any architectural environ as well as being an eye-catching object. Pre-wired cables and a twist-locking mechanism ensure an easy installation. CYCLOPS can be customized to required heights and an anchor unit for concrete foundation is available as an accessory. • Designed, Manufactured and tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium and Extruded Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Polycarbonate diffuser. • Post-cured silicone gasket. • High quality LED module and driver. • GFR PA6.6 Terminal block. • Weather proof TPE grommet. • Pre-wired with outdoor cable. • Installation work has to be carried on according to the enclosed product manual.

## Light output 1



2 x LED			
Nominal lamp power	12 W	LOR	42%
Lamp flux	1300 lm	Total flux	1098 lm
Luminous efficacy	108 lm/W	Total power	27 W
CCT	4000 K		
CRI	80		

## Mounting mode

Standing / Bollard

## Shape and measurements

Length: 6.89 in

Width: 6.89 in

Height: 31.51 in

## Adjustability

Fixed

## Electric

System power: 27 W

Controller: DALI

Appliance Class: II

## Protection

IP: 66

IK: 09