


Product data sheet

TONIC SPOT LED1800-930 MT3 SP BK
96665970
THORN LIGHTING



An LED spotlight with spot distribution and integral fixed output control gear, for 100-240V, 50/60Hz supply. Track mounted (or surface mounted using adaptor accessory) via global GA69 3-phase adaptor. Class I electrical, IP20. Body: die-cast aluminium, painted black. Driver box: black polycarbonate. Complete with 3000K LED. Spotlight can be rotated through 350° and tilted up to 90°. Light distribution can be altered by changing the lens and / or using external attachments. Dimensions: Ø95 x 187 mm Total power: 19.6 W Luminaire luminous flux: 1772 lm Luminaire efficacy: 90 lm/W Weight: 1.3 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	19.6 W	CRI	90
Total flux	1772 lm	LOR	100%
Luminous efficacy	90 lm/W	Total power	19.6 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 7.36 in
Diameter: 3.74 in
Weight: 1.3 kg

Design

Material impression: Aluminum
Color of housing: Black

Electric

System power: 19.6 W
Voltage: 100-240 V AC
Appliance Class: I

Protection

IP: 20
Designation labels: CE