Product data sheet


OUTDOOR LIGHTING
V1-S1-00660-40D32-6605030 LEVANTE ROAD 50W 3000K DALI
VARTON



IP 66 IK 03

LED street light luminaire with a concise design. Adjustable spigot. Cast aluminum housing. Application: streets and roads. Installation: pole mounted and side-entry mounted (Ø40mm-48mm/Ø48mm-60mm). Power factor: 0,95 Ingress protection (IP): IP66 Impact resistance: IK03 Protection class: I AC frequency, Hz: 50 Flicker, %: 3 Climatic modification and category of placement: УХЛ1 Color rendering index: 70-79 Nominal voltage, V: 220...230 https://www.varton.ru/products/ulichnoe-osveshchenie/levante/levante-road-dlya-dorogi/svetodiodnyy-svetilnik-varton-ulichnyy-levante-road-50-vt-kronshteyn-60mm-3000-k-ral9003-belyy-muar-/

Light output 1



1 x LED

Nominal lamp power	50 W	LOR	100%
Lamp flux	6100 lm	Total flux	6100 lm
Luminous efficacy	122 lm/W	Total power	50 W
CCT	3000 K		
CRI	70		

Mounting mode

Pole integrated

Shape and measurements

Length: 23.46 in
Width: 5.35 in
Height: 3.98 in

Adjustability

Fixed

Electric

System power: 50 W

Protection

IP: 66
IK: 03