Product data sheet


BERNINA F SKII 0714MM PC 1X19W 090° 1800LM
7086612
PRACHT



IP 65 IK 08

Flat Surface-mounted light BERNINA F SKII 0714mm PC 1x19W 090° 1800lm 4.000K, class II, with TW 5x2,5mm². Die Anbauleuchte BERNINA F SKII: extrem flach und robust, IP65-Schutz, schlagzähe PRACHTOPAL-Abdeckung und einfache Montage – ¬insbesondere geeignet für den Einsatz in Verkehrsbetrieben, Unterführungen, Bahnsteigen, etc. Item number: 7086612 GTIN: 4018098352617 Technical details/specification: Cover made of PC; Housing made of GRP polyester White RAL 9010; 220–240 V 0/50/60 Hz; Energy efficiency class D; Number of light sources / LED rows: 1; IP65; Through-wiring in mm²: 5x2,5; Dimensions: LxWxH: 714mm x 215mm x 85mm; Diameter: mm

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19 W	CRI	90
Total flux	1800 lm	LOR	100%
Luminous efficacy	95 lm/W	Total power	19 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 28.11 in
Width: 8.46 in
Height: 3.35 in
Weight: 4.6 kg

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 19 W
Appliance Class: II

Protection

IP: 65
IK: 08

Other operating numbers

Ambient temperature range: -13...113°F