

Product data sheet

FLAT POLYMERO ALU
311769.002.4
RZB



IP
43

IK
10

Series: Flat Polymero Alu Type of Protection: IP 43, IP 44 Protection Class: I Voltage: 230 V / 50 Hz Base: die-cast aluminium, powder-coated. Diffuser fastening: bayonet lock. Diffuser: opal polycarbonate plastic. LED included. IP rating: IP43 (ceiling mount), IP44 (wall mount). Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 350, H 130 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 1450lm System power: 27W Beam Angle: 121° Unified Glare Ratio: 20,1 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	27 W	CRI	80
Total flux	1450 lm	LOR	100%
Luminous efficacy	54 lm/W	ULOR	11%
		Total power	27 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 5.12 in
Diameter: 13.78 in

Adjustability

Fixed

Electric

System power: 27 W

Protection

IP: 43
IK: 10