Product data sheet


ROTAO60 227-260K-10GEE/830, B
227-260K-10GEE/830
HALLA



IP 20


227-260K-10GEE/830, B Luminaire surface Material of luminaire: Colour of luminaire: Shape of luminaire: Circular Size: 603 x 603 x 65 mm Type of installation: Surface Distribution: Direct Optics type: Opal diffuser Protection class: I Voltage: 220-240V

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	2.3 W	CRI	80
Total flux	212 lm	LOR	100%
Luminous efficacy	92 lm/W	Total power	2.3 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	2.3 W	CRI	80
Total flux	212 lm	LOR	100%
Luminous efficacy	92 lm/W	Total power	2.3 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	2.3 W	CRI	80
Total flux	212 lm	LOR	100%
Luminous efficacy	92 lm/W	Total power	2.3 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	2.3 W	CRI	80
Total flux	212 lm	LOR	100%
Luminous efficacy	92 lm/W	Total power	2.3 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	2.3 W	CRI	80
Total flux	212 lm	LOR	100%
Luminous efficacy	92 lm/W	Total power	2.3 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	2.3 W	CRI	80
Total flux	212 lm	LOR	100%
Luminous efficacy	92 lm/W	Total power	2.3 W

Light output 7 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	2.3 W	CRI	80
Total flux	212 lm	LOR	100%
Luminous efficacy	92 lm/W	Total power	2.3 W

Light output 8 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	2.3 W	CRI	80
Total flux	212 lm	LOR	100%
Luminous efficacy	92 lm/W	Total power	2.3 W

Light output 9 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	2.3 W	CRI	80
Total flux	212 lm	LOR	100%
Luminous efficacy	92 lm/W	Total power	2.3 W

Light output 10 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	2.3 W	CRI	80
Total flux	212 lm	LOR	100%
Luminous efficacy	92 lm/W	Total power	2.3 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 2.56 in

Diameter: 23.74 in

Adjustability

Fixed

Electric

System power: 23 W

Appliance Class: I

Protection

IP: 20