


Product data sheet

APPAREO G2 CIRCULAR WHITE 4000K CLO
53762-402
FAGERHULT



Installation Wire suspension with ceiling bracket and friction lock, is included with the luminaire. External ballast box is mounted directly to ceiling or placed loosely above ceiling. Connection Luminaire is connected in the ballast box with 230 V, built-in LED ballast in ballast box. Cable entry on top or through the knockout in the side. Snap-in terminal block 5x2.5 mm², 1-phase through-wiring possible. Supplied with a 3 m white fabric cord between luminaire and external ballast box. Design Luminaire body in cast aluminium. The luminaire is lacquered in black (RAL 9005) structured or white (RAL 9016) structured. Ballast box in plastic. Louvre Edge-lit clear prismatic acrylic diffuser (PMMA). Average luminance <3000 cd/m². Dimming DALI dimming as standard. Miscellaneous Appareo has side-emitting LEDs, as a result the luminaire's acrylic diffuser is completely transparent when switched off and provides an evenly luminated surface when lit.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	38 W	CRI	80
Total flux	4909 lm	LOR	100%
Luminous efficacy	129 lm/W	ULOR	43%
		Total power	38 W

Mounting mode

Pendant

Electric

System power: 38 W

Shape and measurements

Length: 26.60 in

Width: 26.60 in

Height: 1.24 in

Protection

IP: 20

Adjustability

Height adjustable

Design

Color of housing: Black, White