


Product data sheet

URBINO LED 27W 3250LM 5700K IP66 O8 - FOR TOWN AND LOCAL ROADS GRAY I
130222.5L021.081
LUG



Professional streetlight luminaire for LED light sources. High efficacy to 156 lm/W Mounting: on pillar $\varnothing 60/48\text{mm}$, on pillar $\varnothing 76\text{mm}$ - modification .829, on outriggers $\varnothing 60/48\text{mm}$, on outriggers $\varnothing 76\text{mm}$ - modification .829. Body: high pressure die-cast aluminum. Lateral Surface Wind Exposed: 0.039 m^2 . Power supply efficiency>95% Power: 220-240V 50/60Hz. Lifetime LED (L90): 100 000 h Available on request: DALI, DIM 1..10V, LLOC, twilight sensor, knife switch, 10kV surge protection, NTC. Additional information: Tilt adjustment: -15° to $+15^\circ$ (every 5°). Additional equipment: additional anti-corrosive protection (index extension: .985), access to the driver chamber without the use of tools (index extension: .825), luminaire with holder for mounting on a $\varnothing 76\text{mm}$ pillar (index extension: .829). Other remarks: the pole and boom are not part of the luminaire. Warranty: 5 years. Application: express roads, local roads, town roads, residential area roads, pedestrian crossings, area lighting, avenues, promenades, cycle paths. Type of optics: O8 - for town and local roads

Light output 1 (integrated)



Lamp type	LED	CCT	5700 K
Nominal lamp power	27 W	CRI	70
Total flux	3250 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	27 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 21.65 in
Width: 9.84 in
Height: 3.94 in

Adjustability

Tiltable

Design

Color of housing: Silver gray

Electric

System power: 27 W
Appliance Class: I

Protection

IP: 66
IK: 09