

Product data sheet

INDUSTRIAL HALL REFLEKTOR
921703.003
RZB




IP
65

IK
08

Series: INDUSTRIAL HALL Round highbay luminaire for chain or cable suspension. Robust housing made of die-cast aluminium with eye ring, powder coated. Vertical cooling ribs ensure constant heat dissipation for optimal thermal management. Diffuser made of clear, non-reflecting, single pane safety glass (toughened glass). Reflector made of matt aluminium. Primary light control with high-performance wide-area LEDs and reflector made of matt aluminium to limit glare. Easy to install thanks to 1-point suspension. Suitable for chain or steel cable suspension (to be provided on site). With power cord (1.5 m). Ceiling- and wall-mounting bracket available as accessory. Luminaire with limited surface temperature in accordance with EN 60598-2-24 for use in environments in which a deposit of conductive dust on the luminaire can be expected. Qualified for use in the food and drink industry. Colour: black Diameter: 360 mm Height: 328 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 165 W Rated luminous flux: 22800 lm Beam angle Down: 87° Luminous efficiency: 138 lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP 65

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	165 W	CRI	80
Total flux	22800 lm	LOR	74%
Luminous efficacy	138 lm/W	ULOR	20%
		Total power	165 W

Mounting mode

Pendant

Electric

System power: 165 W

Shape and measurements

Height: 12.91 in
Diameter: 14.17 in

Protection

IP: 65
IK: 08

Adjustability

Fixed