


# Product data sheet

VIGILANT LED HIGH BAY 10250 LUMENS, MEDIUM DISTRIBUTION, POLYCARBONATE DOME LENS  
HEELMC2ADHWNGN  
DIALIGHT



Vigilant LED High Bay 10,250 Lumens 80 Watts 100-277VAC, 120-250VDC Cool White, 80CRI Polycarbonate Dome Lens CE, ENEC EN 60598-1:2015 EN 60598-2-1 (ed. 1), IEC 60598-2-1 (ed. 8) EN 60598-2-24:2013 EN 62471:2008, EN 62778:2014 EN 62493:2015 IEC60068 Salt Spray Testing - Severity 1 D-Marking to EN 60598 2-24 IK10 Medium Distribution IP66/67 LM79 Tested IES File

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 5181 K |
| Nominal lamp power | 79.8 W   | CRI         | 80     |
| Total flux         | 10899 lm | LOR         | 100%   |
| Luminous efficacy  | 137 lm/W | Total power | 79.8 W |

## Mounting mode

Pendant

## Shape and measurements

Length: 15.94 in

Width: 15.94 in

Height: 5.04 in

## Adjustability

Rotatable, Tilttable

## Electric

System power: 79.8 W

Voltage: 240 V AC, 120 V AC, 277 V AC, 110 V AC, 230 V AC

Appliance Class: I

## Protection

IP: 66

IK: 10

## Other operating numbers

Ambient temperature range: -40...149°F