


# Product data sheet

AJ EKLIPTA Ø350 LED 3000K 8.8W  
90193-1005  
LOUIS POULSEN



AJ Eklipsta Design: Arne Jacobsen Concept: The fixture emits soft comfortable light. The glass is designed to provide a uniformly lit surface. The three-layer mouth-blown opal glass shade has a transparent edge, providing a decorative halo of light around the fixture. Finish: White, powder coated. White opal glass. Materials: Ceiling/Wall box: Die cast aluminium or spun aluminium. Diffuser: Mouth-blown white opal glass. Mounting: Terminal block: Ø 220: 3x2,5mm², Ø 350/Ø 450: 5x2,5mm². Looping: Approved, Ø 220 mm: Max. 3x1,5mm², Ø 350/Ø 450: Max. 5x1,5mm². Ballast positioning: In ceiling/wall box. Class: Ingress protection. LED ceiling/wall: IP20. Ø220: IP20. E27 Ø350/450 Ceiling: IP20. E27 Ø350/450 Wall: IP44. Electric shock protection I w. ground. Sizes and weights: Width x Height x Length (mm) 220 x 105 x 220 Max 0.6 kg 450 x 100 x 450 Max 6.2 kg 350 x 100 x 350 Max 3.6 kg Information: Only Wall mounted E27 versions for outdoor use. For LED fixtures without glass or LED replacement kits please contact Louis Poulsen. The innovation of the LED technology is constant. The specifications mentioned are based on present technology. Ø220: Compatible with leading edge mains dimmers. Please note that low power consumption on some products can affect dimming properties.

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	8.8 W	CRI	90
Total flux	657 lm	LOR	69%
Luminous efficacy	75 lm/W	Total power	8.8 W

## Mounting mode

Wall mounted

## Shape and measurements

Height: 3.94 in  
Diameter: 13.78 in

## Adjustability

Fixed

## Electric

System power: 8.8 W  
Appliance Class: I

## Protection

IP: 20