


Product data sheet

QAW009ML-SI-BM
QAW009ML-SI-BM
RP-TECHNIK




Round metal luminaire for general lighting and the lighting of escape and rescue route according to DIN EN 60598-1, DIN EN 60598-2-22 and EN 1838. This luminaire is designed for use with central battery systems. The LED-luminaire is operated with 26W, 1.600lm and light colour 4000 Kelvin. On mains failure the central battery system continues the supply of the emergency luminaire. On mains operation or failure the luminaire, supplied by the central battery system, operates at 100% luminous flux. This luminaire is equipped with a motion sensor.

Light output 1



1 x LED			
Nominal lamp power	26 W	LOR	48%
Lamp flux	2300 lm	Total flux	1094 lm
Luminous efficacy	88 lm/W	Total power	27.2 W
CCT	4000 K		
CRI	80		

Light output 2 (emergency)



1 x LED			
Nominal lamp power	26 W	LOR	48%
Lamp flux	2300 lm	Total flux	1094 lm
Luminous efficacy	88 lm/W	Total power	1 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted, Wall recessed

Shape and measurements

Height: 4.45 in
Diameter: 15.55 in

Adjustability

Fixed

Electric

System power: 28.2 W
Appliance Class: 0

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 20

IK: 03

Designation labels: CE

Other operating numbers

Ambient temperature range: -4...86°F