


# Product data sheet

AFP S 24L50-740 EWR BPS CL2  
96644737  
THORN LIGHTING



A compact, lightweight, general purpose LED area floodlight. With small body. LED converter configured for power reduction, effective 3 hours before and 5 hours after a calculated midnight, driving 24 LEDs at 500mA with Extra Wide Road light distribution. IP66, IK08, Class II electrical. Body: die-cast aluminium (EN AC-46000), painted grey (RAL9006). Enclosure: 4mm thick toughened glass. Reversable mounting stirrup supplied, optional spigot adaptors available separately for post top mounting. Complete with 4000K LED. Dimensions: 462 x 265 x 139 mm  
Total power: 38 W Luminaire luminous flux: 4692 lm Luminaire efficacy: 123 lm/W weight: 6.2 kg Scx: 0.05 m²

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	38 W	CRI	70
Total flux	4692 lm	LOR	100%
Luminous efficacy	123 lm/W	Total power	38 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 18.19 in  
Width: 10.43 in  
Height: 5.47 in  
Weight: 6.2 kg

## Design

Material impression: Aluminum  
Color of housing: Silver gray

## Electric

System power: 38 W  
Voltage: 230 V AC  
Appliance Class: II

## Protection

IP: 66  
IK: 08  
Designation labels: CE, ENEC