


# Product data sheet

185 LED SHEET STEEL LIGHT FITTING  
185 12L90 T40 (18501 0022)  
SCHUCH



LED sheet steel light fitting, 64 W, 9310 lm, 145 lm/W, Class I, IP65, symmetrical wide beam, 4000 K, CRI $\geq$  80, Ta -40 °C/+55 °C, L70>100000 h (@ Ta max), L80>70000 h (@ Ta max), L90>50000 h (@ Ta 25°C), Pane Safety glass clear, Housing Steel, Colour grey, RAL 7035, central locking system, LABS-tested according to VDMA 24364-C2-L. Extremely flat LED steep roof light fitting, ball-proof with sheet steel housing without external clips. Frameless clear tempered safety glass, central locking system with internal hinges. Powder-coated sheet steel reflector with Zhaga LED modules, frosted LED covers and ECG with overload and short-circuit protection. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting). Length 1204,00 mm, Width/Diameter 282,00 mm, Height 99,00 mm, Net weight 13,67 kg.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	64 W	CRI	80
Total flux	9310 lm	LOR	100%
Luminous efficacy	145 lm/W	ULOR	7%
		Total power	64 W

## Mounting mode

Ceiling mounted, Pendant, Contact rail, Wall mounted

## Shape and measurements

Length: 47.40 in  
Width: 11.10 in  
Height: 3.90 in

## Adjustability

Fixed

## Design

Color of housing: Silver gray

## Electric

System power: 64 W  
Appliance Class: I

## Protection

IP: 65  
IK: 07  
Designation labels: CE