

Product data sheet

PRODISC HELIOS MINI BLACK - STANDARD


40008891

PROLUMIA




Light source : LED (type SMD 2835) Beam angle : 90° Color temperature : 3000-3500-4000 K Light output : 410-820 lm Operating temperature : -25°C to +50°C Rated life hours : L80 > 116.000 LED driver (included) : CE Input : 220-240 V AC, 50/60 Hz Wiring class : Class II Power Factor : >0.91

Light output 1




1 x LED

Nominal lamp power	8.5 W	LOR	100%
Lamp flux	820 lm	ULOR	9%
Luminous efficacy	96 lm/W	Total flux	820 lm
CCT	4000 K	Total power	8.5 W
CRI	80		




1 x LED

Nominal lamp power	4 W	LOR	100%
Lamp flux	410 lm	ULOR	9%
Luminous efficacy	102 lm/W	Total flux	410 lm
CCT	4000 K	Total power	4 W
CRI	80		




1 x LED


Nominal lamp power	8.5 W	LOR	100%
Lamp flux	845 lm	ULOR	9%
Luminous efficacy	99 lm/W	Total flux	845 lm
CCT	3500 K	Total power	8.5 W
CRI	80		



1 x LED			
Nominal lamp power	4 W	LOR	100%
Lamp flux	425 lm	ULOR	9%
Luminous efficacy	106 lm/W	Total flux	425 lm
CCT	3500 K	Total power	4 W
CRI	80		



1 x LED			
Nominal lamp power	8.5 W	LOR	100%
Lamp flux	790 lm	ULOR	9%
Luminous efficacy	93 lm/W	Total flux	790 lm
CCT	3000 K	Total power	8.5 W
CRI	80		



1 x LED			
Nominal lamp power	4 W	LOR	100%
Lamp flux	395 lm	ULOR	9%
Luminous efficacy	99 lm/W	Total flux	395 lm
CCT	3000 K	Total power	4 W
CRI	80		

Mounting mode

Ceiling recessed, Pendant, Wall mounted, Wall recessed

Shape and measurements

Height: 2.24 in

Diameter: 11.42 in

Electric

System power: 4-8.5 W

Appliance Class: II