

# Product data sheet

BENTO M

BENTO-M-ASY14-48LED-3000K-4P6S-230 MA


RAGNI



IP  
66

Made of aluminium and featuring symmetrical lines, Bento is a functional luminaire with a minimalist design available in 3 sizes. Rectangular in shape, it has a compartment at the back that houses the control gear, harmoniously joining the lighting part. The fins on the top of the luminaire promote heat dissipation. It has a double compartmentalisation and is fully IP66. Its sleeve is adaptable for side or top mounting (with inclination from -15° to 15°). Bento receives from 12 to 24 LEDs in the S version, 24 to 48 LEDs in the M version and 72 LEDs in the L version, with a colour temperature of 3000 K or 4000 K and offers 3 asymmetric light distributions. The Bento luminaire incorporates the Zhaga standard in its design.

## Light output 1



### 1 x LED

Nominal lamp power	66 W	LOR	100%
Lamp flux	9847 lm	Total flux	9862 lm
Luminous efficacy	149 lm/W	Total power	66 W
CCT	3000 K		
CRI	70		

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 27.56 in

Width: 11.81 in

Height: 3.94 in

## Adjustability

Fixed

## Electric

System power: 66 W

## Protection

IP: 66