


Product data sheet

SRT-SYSTEM IP20-SRGVCB XP/1500 LED - GERÄTETRÄGER VARIABEL CENTRAL.LINE.OPTIC | DEVICE MOUNT VARIABLE...
4000 840 (PHI-EL=1035LM) DALI2 NL-3H VW RAL 9016 (SRT+19515015000)
REGIOLUX



SRT-Quick-fit mounting system, Variable device mount, Modullänge/1500. Device mount made of a galvanised, profiled steel sheet; surface coated with polyester resin. Tool-free attachment with design-integrated pressure caps guarantee protection against theft and dismantling. Variable position on the mounting rail. Housing colour traffic white RAL 9016. Performance level: Xtreme Performance (XP) - For the most demanding tasks, the best possible performance, durability and warranty period at the highest level, Light distribution direct wide distribution by means of Central.Line.Optic of PMMA plastic, the lens optics ensure absolute ease of assembly and are simple to maintain thanks to the easily cleaned surface. The compact 1-row arrangement of the lenses ensures that the dots merge into a line with a homogeneous appearance in the object. The light source and driver are removable in accordance with the EU 2019/2020 ecodesign requirements and can be replaced in the factory. Electrical connection by means of a 1m connection cable for variable device mount positioning with a 7-pin, quick-fit plug connector in the light run with free phase pre-selection; With 3h emergency lighting battery; Luminaire status by visible status LED in luminaire (NL-B3); Luminous flux in emergency light mode 1035 lm. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system. Dimensions (LxWxH): 1531mm x 55mm x 37mm Beam angle: 95°(C0)/95° (C90) Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 4000K Colour tolerance: 3SDCM Photobiological safety (Luminaire): RG0 LED service life: 100000h L90/B10 (Tq 40°C), 100000h L90/B50 (Tq 40°C) Nominal luminous flux: 4415lm Nominal luminous flux-emergency lighting mode: 1035lm Luminaire luminous efficiency: 214lm/W Control gear: Electronic driver DALI2 + 3h emergency lighting (1 pcs.) System output: 21W Energy efficiency class/light source: B Mains voltage: 230V Mains frequency: 50Hz Impact resistance (IK rating): IK03 (5°C bis 40°C) Ambient temperatur: ta 5°C to 40°C Special properties: Ready for IoT UGR lat./long.: max. 20.5 / 21.8 Certification mark: IP20, Protection class I, F, HACCP DIN10500/Food/IFS-application-related suitability (see certificate)/BRC, Indoor, CE Warranty period: 10 years Regiolux GmbH Type: SRGVCB XP /1500 LED 4000 840 DALI2 NL-B3 vw RAL 9016 Article number: 19515015000 Product deep link: <https://www.regiolux.de/en/article/19515015000> General warranty conditions: www.regiolux.de/en/Service/Warranty

Light output 1 (integrated)



Lamp type		CCT	4000 K
Nominal lamp power	20.7 W	CRI	80
Total flux	4415 lm	LOR	100%
Luminous efficacy	213 lm/W	Total power	20.7 W

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 60.43 in
Width: 2.48 in
Height: 2.64 in

Electric

System power: 20.7 W
Appliance Class: 0

Design

Color of housing: White

Protection

IP: 20

IK: 03

Designation labels: CE