Product data sheet


CIRCULAR INWARD Ø600 SURFACE
CD4A-00X9AZDU05
LEDSC4



IP 20

LedsC4 Circular Inward ø600 Surface CD4A-00X9AZDU05V1 Pendant for indoor use. For uplighting and downlighting. Structure finish: Black. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 3.4 Product width or diameter (mm): 636 Product height (mm): 3000 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEAN WELL. Maximum power of light source: 36.4W. Colour temperature: 4000K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 11.4. Photobiological risk: RG1. Real flux (lm): 2611. Real lm/W: 67. Voltage / frequency range: 90-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 39. Power factor: 0.90. Dimmable equipment included: DALI-2.

Light output 1



1 x LED

Nominal lamp power	36.5 W	LOR	100%
Lamp flux	2611 lm	ULOR	50%
Luminous efficacy	72 lm/W	Total flux	2611 lm
CCT	4000 K	Total power	36.5 W
CRI	90		

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 23.62 in
Width: 23.62 in
Height: 1.18 in

Adjustability

Fixed

Electric

System power: 36.5 W
Appliance Class: I

Protection

IP: 20