



Product data sheet

161 LED DAMP-PROOF LIGHT FITTING
161 12L42 AUS KE VP (16117 0549)
SCHUCH



LED damp-proof light fitting, 27 W, 4240 lm, 157 lm/W, Class I, IP65, symmetrical wide beam, 4000 K, CRI \geq 80, Ta -20 °C/+40 °C, L70>100000 h (@ Ta max), L80>70000 h (@ Ta max), L90>50000 h (@ Ta 25°C), Diffuser PMMA satined, Closure Stainless steel (1.4571), Housing Glass fibre reinforced polyester, Colour grey, for unprotected outdoor areas, additional overvoltage protection. Sturdy LED damp-proof light fitting for application in unprotected outdoor areas. Highly impact-resistant glass fibre reinforced polyester housing and frosted PMMA diffuser with high impact and UV resistance. Captive clips, multi-part, incl. two safety clips, silicone gasket and pressure compensation system. Powder-coated aluminium reflector with highly efficient Zhaga LED modules and ECG with overload and short circuit protection. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting). Length 1272,00 mm, Width/Diameter 116,00 mm, Height 125,00 mm, Net weight 2,70 kg.

Light output 1 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 27 W | CRI | 80 |
| Total flux | 4240 lm | LOR | 100% |
| Luminous efficacy | 157 lm/W | ULOR | 7% |
| | | Total power | 27 W |

Mounting mode

Ceiling mounted, Pole top mounted, Wall mounted

Shape and measurements

Length: 50.08 in
Width: 4.57 in
Height: 4.92 in

Adjustability

Fixed

Electric

System power: 27 W
Appliance Class: I

Protection

IP: 65
IK: 05
Designation labels: CE