

Product data sheet

ELN L30 MP
ELISIAN
DEXTRA




IP
40



Elisian - Ø320mm, IP40 Recessed downlighter with spun aluminium housing, four point steel spring mechanism and microprism diffuser.
Options: E3 - Emergency control gear (436 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest STR - Reacta-Link Wireless Self test S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function) R44 - Daylight regulating and Occupancy Sensor RAS - Reacta Air Wireless Presence & daylight RLS - Reacta-Link Wireless Presence RCS - Reacta-Control Wireless, Presence

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19.82 W	CRI	80
Total flux	2306 lm	LOR	100%
Luminous efficacy	116 lm/W	ULOR	4%
		Total power	19.82 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 2.56 in
Diameter: 12.60 in

Adjustability

Rotatable, Tilttable

Electric

System power: 19.82 W
Ballast: ECG

Protection

IP: 40
Designation labels: CE