
Product data sheet

PURE3.QUIET SUSP. ANTHR./SILVER M DI/ID HE PRISM P33H18R-QASIC2930L3T OHNE FOLIE/WITHOUT FOIL


PLANLICHT



IP 20


LED LO 3000K 76,3W 11406lm DALI CRI90 ¹Values without foil [Luminaire is delivered with optional satined-foil for increased homogenity. The light distribution is thus influenced and the luminous flux is reduced by 7,4% https://katalog.planlicht.com/en-gb/search?q=pure%203

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	38.15 W	CRI	90
Total flux	5703 lm	LOR	100%
Luminous efficacy	149 lm/W	ULOR	34%
		Total power	38.15 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	38.15 W	CRI	90
Total flux	5703 lm	LOR	100%
Luminous efficacy	149 lm/W	ULOR	34%
		Total power	38.15 W

Mounting mode

Pendant

Shape and measurements

Length: 27.95 in

Width: 71.57 in

Height: 3.94 in

Adjustability

Fixed

Electric

System power: 76.3 W

Protection

IP: 20