


Product data sheet

LTUB60 SUT 840 2200 9NW TECH WH
L61ST084MOTE940NW
LAMP




IP
20

IK
07

Luminaire to be installed on a suspended rail, model LAMPTUB 60 TECH by LAMP. Made of 80% recycled aluminium extrusion, with circular section of 60mm and length 840 mm, with matt black reflector ULTRA COMFORT and optics for light distribution control and low glare level, less than UGR16. Model for MID-POWER LED, with colour temperature 4000K and CRI90. Built-in electronic wiring. With IP20, IK07 degree of protection. Insulation class II. Photobiological safety group 0. Lifetime:50000 L90 B10 Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette. Compatible with Lamp Nomadic system.

Light output 1



| | | | |
|--------------------|---------|-------------|---------|
| 1 x LED | | | |
| Nominal lamp power | 13.7 W | LOR | 99% |
| Lamp flux | 1320 lm | Total flux | 1311 lm |
| Luminous efficacy | 96 lm/W | Total power | 13.7 W |
| CCT | 4000 K | | |
| CRI | 90 | | |

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 34.02 in

Width: 2.76 in

Height: 2.56 in

Adjustability

Fixed

Design

Color of housing: Black, White

Electric

System power: 13.7 W

Appliance Class: 0

Protection

IP: 20

IK: 07